



LED Wall Pack Series
125 Watt – 120Vac or 347 Vac
Model #: RL-WP125-120 / RL-WP125-347

Maintenance free outdoor 125 watt LED wall pack. High quality aluminum alloy housing with corrosion resistive coating, complete with stainless steel bolts and screws. Tempered glass lens with rubber gasket. Replaces the equivalent of a 400 watt HPS. Energy savings of up to 70% when compared to equivalent incandescent lighting. IP 65 rating.

Multiple Applications

Ideal for:

- Large area lighting;
- Security Lighting

Specifications

Model Number	RL-WP125-120 / RL-WP125-347
Input Voltage	110-240 Vac or 347 Vac, 50-60 Hz
Input Current	1.0 A-120 Vac / 0.36 A-347 Vac, 50-60 Hz
Power Consumption	125W, PF≥0.973
LED Chip	SMD Cree
Lumen Output	10,200 lm
Luminous Efficiency	85 lm/w
Color Temperature	Natural White (4100K)
Color Rendering Index (CRI)	>84
Beam Angle	120°
Estimated Lifespan	50,000 hours
Driver	Meanwell
Driver Output Voltage	36 Vdc
Driver Output Current	2500 mA
Operating Temperature	-20°C to +40°C
Materials	Al. Alloy, Tempered Glass & Stainless Steel
IP Rating	IP65 (suitable for wet locations)
Certifications	 (E359673), CE, RoHS, LM79, LM80
Color of Lamp Housing	Brown
Dimensions (L x W x H -See Line Diagram)	452 mm x 249 mm x 330 mm
Weight	8.8 kg
Warranty*	3 years

* Details of our warranty information are available at www.RhynoLED.ca/warranty

All information contained within this documentation was derived from information and tests Rhyno LED Lighting Solutions Inc believes to be accurate and reliable; however, the accuracy and/or completeness of the information relied upon cannot be guaranteed. As the use and conditions of use are beyond the control of Rhyno LED Lighting Solutions Inc, the purchaser/end user must determine the suitability of the product for the intended use and assumes all risk and liability.

Your Imagination Is Your Only Limitation